

## LED Lighting

## LED Downlights DLA-G2-100mm series



### Features

- Replacement for downlight with compact fluorescent lamps
- Complete solution: module, driver, reflector and trim ring
- Tool-free assembly, simple as push and rotate
- Spring clip pre-assembled
- Ripple current  $\pm 5\%$  and UGR19 (specific types)
- Fit for ceiling cut-out 100 mm
- Luminous flux typ. 1,000 lm
- Approved emergency solution with EM converter LED
- High system efficacy up to 111 lm/W
- Optional reflector solution with 60° and 90°
- Small colour tolerance MacAdam 4
- Nominal life-time 50,000 h (L70/B50)
- 5-year guarantee

### Description

The DLA-G2-100mm series LED downlights are designed as replacements for traditional compact fluorescent downlights and fit a standard 100mm cut-out. Comprising of high power COB LED and approved LED driver the downlight is powered directly from the AC mains supply.

### Specifications

Model	Power (W)	CCT°K	Total Flux (lm)	CRI (Ra)	Beam Angle
DLA-G2-100NAW-xx-230v	10W	4000K	1000	>90	60°, 90°, 100°
DLA-G2-100WW-xx-230v		3000K	1000		

Suffix: Beam angle: 60°, 90°, 100°

### Dimensions

